WORK ALREADY ACCOMPLISHED ON THE PANAMA ROUTE.

Report of Gen H. L. Abbot, U. S. A. on Conditions as He Found Them During the Years 1896-08.

WHAT THE OLD COMPANY DID

VAST AMOUNT OF ACTUAL CONSTRUC-TION WAS COMPLETED.

Data Secured for Successful Carrying on of the Enterprise-Statistics and Requirements of Project.

Canal Company rose, phoenix-like, from the wreck of the De Lesseps enterprise, it succeeded not only to valuable franchises and conconcessions, but to a vast amount of work

already accomplished; to a colossal aggregation of plant and appliances for the carrying on to completion of the work, and-the most essential requirement of all-a broader knowledge of the needs and possibilities incident to the work at hand than the old company had possessed.

When the new company put its force of 4,000 men at work it found two-fifths of the entire canal work actually completed, according to the estimates of its own engineers. Of the 46.5 miles the portions adjacent to the sea at both ends had been excavated, and on the higher levels beyond the twenty-eighth mile from the Atlantic a large amount of work had been done. At Culebra, the highest point on the canal, the cut was carried, by Dec. 1 of that year, to a depth of 164 feet. The expenditures of the old company, as compiled from the report of the receivers, were \$156,400,000, and of this sum the cost of excavation and embankments was \$88,600,000.

On the second point-that of facilities for carrying on the work-it is not necessary to go to the report of the receivers, nor yet to the prospectus of the new Panama Canal Company, issued on Dec. 26, 1898. Richard Harding Davis, in his "Three Gringos in Venezuela and Central America," declared that the pathos of the situation was not that the works were rotting and the machinery rusting, but that each and every bit of the appliances for carrying on the work was kept as if on exhibition, in complete readiness for an army of workmen to take hold and push the work

Regarding the third point, the company stated in its own behalf:

"At the present time (December of 1898) the topography of all the grounds involved in the project, and the character of the materials to be encountered, are actually known and delineated; deep and extensive excavations, as well as numerous soundings and borings have made known the subterranean strata underlying the surface, and by those means no doubt is left of the soundness of the materials through which the canal is to be dug to great depths, and on which the foundations of the locks, dams and other structures are to be established."

One of the first acts of the new company was to appoint a commission composed of and for nearly two years this body of experts went over the ground, investigating be done without waiting for their report.

Third in the list of these men was Brigadier General Henry L. Abbot, corps of engineers, U. S. A., retired, who signed the report of the commission, and later summarized its findings in an article published in the Engineering News on Oct. 6, 1898. The article sets forth the exact status of the work at that time, and as comparatively little has been done since ther, except to keep the works in order and to prevent, so far as possible, the dethe merits and demerits of the Panama and Nicaragua routes.

STATISTICS OF CANAL WORK.

Comparison with Other Similar En-

terprises-Work of Old Company.

After the failure of the old Panama Canal Company, in February, 1889, the property passed into the hands of a receiver, who, seeking to save from ruin the vast number of subscribers of moderate means, referred the technical problems to a "Comite d'Etudes" selected from amongst the best engineers of France. In May, 1890, this commission made an able report, indicating the numerous points which demanded further investigation before final plans could be judiciously adopted, but suggesting the general features of such a plan, based on a study of all existing data. To make these further investigations a new company was organized in October, 1894; and since that date it has quietly prosecuted its labors and has now collected all the information needed to command the confidence of engineers in its definite project. It is to set forth this project, and to indicate its superiority to anything possible in Nicaragua, that the present article is written. It may be proper to add that the writer, as a member of a technical commission of engineers, made last spring a careful examination of the entire route of the Panama canal, and is thus possessed of definite personal information, in some degree assisted by having formerly traversed Nicar-The following are the essential features of this project, indorsed, with some possible future modifications in details, by a comite technique, containing French. English, German, Russian and American engineers, among them the chief engineers of the Manchester and of the Kiel ship canals.

The original plan contemplated placing the canal in the bed of the Chagres, and conducting the river to the sea through artificial channels. This project was long ago definitely abandoned, being replaced by the familiar system of locks and dams which has been so often successfully appiled to other rivers. Careful measurements and studies of the regimen of this torrential stream have shown the system to be entirely applicable to it, and that none of the constructions demanded will exceed the limits of recognized engineering practice. To these advantages it should be added that two good harbors already exist at the Atlantic and Pacific terminals; that an American railway is in active operation is needful.) The length of these levels in parallel and in close proximity to the tensive preparations have already been below the level of the soft upper strata, of the river and fifty meters (164 feet) above hand exposing rocks in the navigable bed made for accommodating the army of which gives so much trouble by sliding,

laborers which will be required on any and is now and will continue to be in an The cross-section conforms to the condiisthmian canal. These reasons certainly indurated clay schist, requiring blasting, tions of recent engineering practice. demand that the comparative merits of and passing to veritable rock. Serious To facilitate construction, a tunnel 300 this route should be considered before trouble need no longer be apprehended here. meters (984 feet) long and seventy-five adopting another location for the canal This problem has been studied most thor- square meters (807 square feet) in crossnow generally believed to be essential to oughly by the new company-involving the section will be driven through the ridge to

NICARAGUAN CONDITIONS.

time would entail veritable disasters.

distinctly inferior. Two ports must be arti- at a level of forty-one meters (134.5 feet.) ficially prepared; one at least of great of railroad must be built, mostly travers- feet) is adopted for the central cut, and 3,000 | proval of the comite technique. ing a wilderness. Almost nothing has been | meters (9,840 feet) for the rest of the line, will unite to aggravate the difficulty of meters (262.4 feet.) Even with the large shipping in transit. The length of the route | standard curves adopted, suitable enlarge- out precedent for canal purposes. is about four times that of the Panama | ments will be provided to render the route canal, adding proportionately to the time of | perfect in this important detail, in respect | manded, quite without precedent in our either Kiel or Manchester. canal construction, besides several miles of huge embankments in the San Francisco

CROSS SECTIONS. basin, where the foundations are extremely varies in different localities, as shown in lowing: bad, and where a rupture at any future | the following table: The depth is uniformly nine meters (29.52 feet), and the side But passing from generalities, the details | slopes usually three base to two height in | of the Panama project will first be con- earth, and two base to three height in rocky cuts. In respect to berms and revet-

SENATOR JOHN T. MORGAN



Senator Morgan has long been noted for his strenuous advocacy of a canal connecting the Gulf of Mexico with the Pacific ocean. He holds out for the Nicaraguan route, and threatens to block the Panama project if he can find a way.

seventy-five kilometers (46.5 miles), of by the recent International Congress which five (3.1 miles) lie in the Bay of Panama, between Isle Naos and La Boca. Of the seventy kilometers (43.4 miles) of inland construction, twenty-four kilometers (14.88 miles) on the Atlantic side (between Colon and Bohio) and seven kilometers (4.34 miles) on the Pacific side (between La Boca and Miraflores) will be at the sea level, and of this distance about twenty-five kilometers the most eminent engineers in the world, (15.5 miles) are now essentially excavated; thus there remains only thirty-eight kilometers (23.5 miles) to be traversed by the aid every phase of the situation, while the com- of locks; and here also so much actual pany went ahead with such work as might | work has been done that no visitor can tom, to enable vessels to pass each other, pass over the line without appreciating that the canal can no longer be regarded

as an experiment. Of these thirty-eight kilometers between Bohio and Miraflores, the first twenty-two (13.64 miles) extending from Bohio to Obispo, will traverse a vast lake 5,500 hectares (13,-585 acres) in extent, created in the valley of having a serviceable length of 225 meters the Chagres by a dam at Bohio. Its level above the sea will range between a minimum of sixteen meters (52.48 feet) and a maximum of twenty meters (65.60) feet), the (32.8 feet) at the middle. The smaller chamterioration of the plant, it is reproduced normal level being seventeen meters (55.76 ber has the same serviceable length, with here as being a concise description of the feet.) A reservoir of 150 million cubic property to which, in all probability, the meters (52,950 million cubic feet) is thus United States will succeed. It also sets | provided to control in part the floods of the forth briefly a comparative statement of river. Access to the lake will be furnished by two double locks at Bohio.

There thus will remain to be considered only the sixteen kilometers (ten miles) lying between Obispo, where the canal leaves the Chagres river and Miraflores, where sea-level is reached. This section includes the continental divide at the Culebra, approached on the side of the Atlantic by the valley of the Obispo, a tributary of the Chagres, and on the Pacific by the valley of the Rio Grande. The great economic problem to solve has been to determine the most advantageous level for the bottom of the canal between these two points, with a view to afford the best balance be tween the cost and the time of constructing the locks and dams on the one hand and

deep cutting on the other. TO REGULATE FLOODS. This problem, with its adjuncts of how to best supply the summit level during the dry

season, and how to regulate the floods of the Chagres during the rainy season, and how to provide hydraulic power for lighting and operating the canal at all seasons. has been most thoroughly studied on the spot by the new company since its organization in 1894. Space is lacking to detail the trivial excavations, aggregating three millions cubic meters, the surveys, the borings, the gaugings of the water courses and the many other details which have been investigated in the most elaborate manner. Suffice it to say that, after comparative estimates of sixteen variants, the comite technique has advised the adoption of a level of 20.75 meters (sixty-eight feet) above mean tide, which, should experience in the active prosecution of the work render it expedient, will admit of modification, either by adding two more locks, raising the level of the cut to 29.5 meters (ninety-seven feet). or of suppressing one or perhaps two locks.

and thus reducing it to ten meters (thirtythree feet.) This definite plan, placing the bottom the canal at a level of 20.75 meters, involves two double locks at Obispo, raising the water surface at the summit level to a maximum of 31.25 meters (102.5 feet) and a minimum of 29.75 meters (97.58 feet); one double lock at Paraiso dropping these levels to 23.25 meters (76.26 feet) and 22.25 meters (72 98 feet), two double locks at Pedro-Miguel, dropping them to 6:25 meters (20.5 feet) and 5.25 meters (18.22 feet); and a tidal lock at Miraflores, where the water level varies between three meters, or ten feet, above, and three meters below mean tide. (On the Atlantic side the tidal oscillation is only a few inches, and no such provision every case exceeds two kilometers (1.24 line of the canal throughout its entire ex- miles), thus avoiding trouble from oscillatent; that about 40 per cent. of the whole | tions due to lockages. In reference to the length has been actually excavated, and deep cutting at Culebra-the bugbear of that great progress has been made on the former days-it is only needful to say that intermediate portions; and finally, that ex- the excavation has already been carried forty-one meters (134.5 feet) above the bed

Colon to Boblo. Lake Bohio (minimum)..571.5 Paraiso to Pedro Miguel. 406.5 Pedro Miguel to Mira-Miraflores to La Boca\*..720.0 Bay of Panama (low \*Low tide.

(31.16 feet) at the sides, and ten meters intermediate gates to reduce it to 130 meters. (426.4 fect) when desired; a width of eigh-

teen meters (59.04 feet); and the same depth as the other. The larger will be constructed first, together with the foundations and head of the smaller, thus permitting the latter to be completed after opening the canal to traffic. The maximum lift has been fixed at nine meters (29.5 feet), except at Bohio, where provisions for ten meters (32.8 feet) will be made, for use during extreme floods of the Chagres, which last only for a few hours.

protect the structure against shocks.

at Obispo, at Paraiso, at Pedro-Miguel and kilometers (ten miles) above, on the upper Chagres. Of these only the first and last masonry and one of earth.)

GREAT BOHIO DAM. The dam at Bohio will be of earth, abutting on conglomerate rock at the sides, and founded on a compact bed of clay, believed to be diluvial. The length of the crest will above the bed of the river, twenty-three meters (75.4 feet), and above the foundation 28.5 meters (93.5 feet). The width at the crest which rises three meters (ten feet) above the highest level of the lake, will be fifteen meters (49.2 feet); the upstream slope wide, the whole riveted with stone laid dry; the downstream slope has a height of two on a base of three, with one berm three meters wide, and is supported by a mass of loose rock rising to a sufficient height to protect the dam if, in spite of all precautions, it should chance to be overtopped by a sudden flood during construction. A puddled core, and a concrete wall at the upper toe, will cut off any possible leakage. The mass of the dam will be of excellent materials found in the close vicinity. During

comite technique.

Engineers at Brussels, will be followed. Earth. Rocky cuts. Bottom Bottom Sec. width, Sec. width, sq. m. mtrs. sq m. mtrs. 379.5 280.2

Enlargements 600 meters (1,968 feet) long and sixty meters (196.8 feet) wide at botwill be provided in the canal at intervals of about eight kilometers (4.96 miles); but immediately above and below the locks these dimensions will be raised to 700 meters | 700 cubic meters (24,710 cubic feet) by a (2.296 feet), and sixty-two meters (203.4 feet.) The Locks.-The locks, all founded on rock, are to be double, the larger chamber (738 feet) a width of twenty-five meters (82 feet), and a depth of 9.5 meters

The gate will be pivoted single leaf type, and water will be supplied by pipes buried in the lock floors and delivering on each side and throughout the whole length of the chamber, the flow being regulated by valves of the low level cylindrical pattern. Entrance to the chambers from either direction will be facilitated by crib piers, sixty meters long, with detached heads to

The Dams, .- There will be six dams, five ocated on the line of the canal at Bohio, at Miraflores, and one at Alhajuela, sixteen need be considered, as the other four are minor affairs presenting no engineering difficulties (three of them are to be. of

ample provisions by reservoirs for com-

compact rock. The length of crest will be artificial height, is essential to avoid on 285.5 meters (936.4 feet); and the height the deepest part of the rock foundation. of the San Juan. These difficulties are ag-

meet the needs of our Atlantic and Pacific removal of about two million cubic meters a bend of the river below, and a temporary of material, the sinking of many pits and | dam will divert into it the minor flood disborings, and the construction at the worst | charges of the river. To meet the case of In Nicaragua the general conditions are | point of a tunnel 210 meters long (689 feet) | larger floods, the dam will be raised alternately on the two sides, thus allowing space In locating the line of the canal, great | for a portion to be overflowed without inpractical difficulty, since nature has al- care has been taken to avoid abrupt curves, terrupting the work. These details have ready closed the harbor. About 120 miles A minimum radius of 2,500 meters (8,200 been carefully studied, and meet the ap-

Engineers will recognize the immense addone in the way of construction or of pre- except near Bohio, where radii of 2,500 vantages possessed by the Panama route, paration for the work. Of the whole length | meters and 2,000 meters (6.500 feet) occur | in the matter of dam construction, over the of 176 miles, sixty-eight miles follow the in enlargements having a bottom width of conditions found at Nicaragua, where the bed of a crooked river, where the prevail- | sixty-two meters (23.4 feet) and near Obis- | diversion of the San Juan river is admitted ing trade winds and the currents resulting | po. where one radius of 1,700 meters (5,576 | to be impracticable, and where the foundafrom the whole outflow of Lake Nicaragua | feet) occurs with a bottom width of eighty | tions present extraordinary difficulties and demand an unusual structure quite with-

Regulation of the Chagres River .- This subject, comprising the control of the floods passage; finally, at least one dam is de- to which it is more favored by nature than and the supply of the summit level, has received the elaborate investigation demanded by its importance. Space is lacking for de-The cross-section to be given the canal tails, but the general features are the fol-

CHAGRES RIVER LEVELS. At Alhajuela the low water surface of the river is twenty-eight meters (91.84 feet) above sea level; at Gamboa, fourteen meters (forty-six feet), and at Bohio, The Canal Proper,-The total length is ments, the latest practice, as recommended naught meters. The mean annual discharges at these three points respectively are sixty-three cubic meters (2,224 cubic feet), eighty-four cubic meters (2,965 cubic feet), and 121 cubic meters (4,261 cubic feet) per second. During the three low water months (February, March and April) these mean volumes fall to twenty-seven cubic meters (953 cubic feet), thirty-one cubic meters (1,094 cubic feet), and thirty-nine cubic meters (1,376 cubic feet), the minimum being nine cubic meters (318 cubic feet), ten cubic meters (353 cubic feet), and fourteen cubic meters (459 cubic feet.) The maximum flood volumes closely estimated on the basis of the floods of 1879, the largest within the memory of the inhabitants, is at Gamboa, 2,040 cubic meters (57,539 cubic feet) per second, and at Bohio 3,100 cubic meters (109,410 cubic feet). The floods of the river, great and small, are all of the torrential type, resulting from the heavy and wide- ninety-three inches, or only about 50 per spread tempests of the rainy season. Their | cent. more than on our gulf coast, while in uration is extremely short, rarely exceeding in the greatest floods forty-eight | including the Ochoa dam and in the San hours at Gamboa and ninety-six hours at Francisco embankments, lie a district Bohio. The maximum heights ever attained above the low water stage are about eleven meters (36.1 feet) at Gamboa, and twelve meters (39.36 feet at Bohio. These figures, resulting from years of patient and careful observations, have furnished the basis for solving the two great questions of river regulation presented by the problem of the canal.

Upon an estimate, known to be safe, of allowing 1,000 cubic meters (35,300 cubic feet) per second to freely pass Gamboa and 1,200 cubic meters (42,360 cubic feet) to freely pass Bohio, reservoirs to contain 100 million cubic meters (3.530,000,000 cubic feet) above Alhajuela, and 150 million cubic meters (5,295,000,000 cubic feet) above Bohio are needful to restrain the greatest known floods; and these are provided by the dams already described. In no other than the flood of 1879 would so large volumes be de-

The level of these lakes to be regulated by overflow weirs of the Stoney type, which have given perfect satisfaction on the Manchester canal, and which have the great low the water surface without serious leak-

Alhajuela will follow the bed of the Chagres to Lake Bohio. The volume of to escape from the latter, will pass by two overflow weirs-one to the left of the canal, discharging 500 cubic meters (17,650 cubic feet) per second through the bed of the Chagres and its derivation, and the other route also separated from the canal.

DRY SEASON NEEDS. To supply the summit level during the season of low water, the inflow of twenty cubic meters (706 cubic feet) per second will be required. To provide 7,000 horsepower for lighting the canal and operating the gates, fifteen cubic meters (530 cubic feet) per second are demanded, falling thirty-two meters (105 feet) at Alhajuela, and sixteen meters (52.5 feet) at Bohio, and acting on turbines driving dynamos to transmit the power in the form of electricity. The reservoir capacity, in excess of the low water flow of the Chagres, to supply these two needs, is 130 million cubic meters (4.589 million cubic feet). The area of the lake above Alhajuela is 2,300 hectares (5,-750 acres) at the level of sixty-one meters (200 feet) above tide water and 3,000 hecwater nine meters (29.5 feet) deep to contain 100 million cubic meters for flood storage and 130 million for low water supply Upon this basis the capacity of the lake has been regulated.

To transport the needful volume of water (twenty cubic meters per second) from Alhajuela to the summit level, a feeder sixtecn kilometers (ten miles) long will leave the lake at a level of fifty-eight meters (109.3 feet) above tide, and follow the left bank to a lateral valley, discharging gently into the summit level about a kilometer (0.62 miles) from the locks at Obispo. The fall between the lake and point of delivery will be seventeen meters (55.8 feet), and the cross-section is established to carry from twenty-five (882) to forty cubic meters (1,412 cubic feet) per second, with a view to meeting all possible contingencies of a largely increased traffic. At these heights water will flow into the canal even if the higher summit level should finally be found to be more advantageous. The feeder traverses be 392 meters (1,286 feet); the extreme height | a difficult region and will be costly, but all details of construction have been success-

fully elaborated. At Lake Bohio, as already stated, a capacity of 150 million cubic meters i needed for storage during great floods, and to assist the overflow weirs in regulating has a height of one on a base of three, with the level during the sudden influx of four berms each three meters (ten feet) smaller floods. This volume calls for a layer of water three meters (ten feet) deep, and another meter has been added, to contain a reserve for supplying evaporation in the lake during the dry season.

SOLUTION POSSIBLE.

From the foregoing it will be seen that

the hydraulic problems presented by this turbulent river-at one time regarded as so serious-admit of satisfactory solution. This is hardly the case in Nicaragua, where one of the great difficulties of the project is the regulation of a summit level depending on construction the river will be diverted that of an immense lake 2,700 square miles through the rock cut for the locks, with in extent, receiving directly the drainage of 8,700 square miles of territory, together bating larger floods. All the details have with that of 2,250 square miles more through been carefully studied, and the project has the tributaries of the San Juan river above received the unanimous approval of the the dam at Ochoa, conditions which render the ordinary method of storage reser-The dam at Alhajuela will be of concrete voirs wholly inapplicable. Nevertheless a masonry founded on and abutting against | delicate regulation of this level, and at an

the one hand drowning a cultivated dis-

trict on the west shore, and on the other



FRENCH LICK, SPRINGS HOTEL THOS. TAGGART PRESIDENT THE IDEAL MISALTH & PLEASURE FAMILY RESORT OF AMERICA. FRENCH LICK THE YEAR PER DAY REDUCES 'ON THE MONON" IN THE WORLD NOW ON SALE ATALL DRUGSTORES PER CASE PER BOTTLE 15° 25° 435° SEND FOR BOOKLET

gravated by the necessity of placing the overflow weirs near Ochoa, at a distance of more than 100 kilometers (sixty-two miles)

from the lake. In this connection it may be noted that in the matter of rainfall the Panama canal is the more fortunate. All the difficult excavations and works of construction, except those near Bohio, lie in the interior where the annual downfall, as determined by thirty-two years of observation, is Nicaragua, the most difficult constructions where the downfall, as determined from the data collected by the Nicaragua Canal Company (about seven years' observations), is 256 inches, or nearly three times as much. Estimates.-This subject has received the mose careful study, both in determining quantities and unit prices. Much valuable data as to the latter, based on actual experience on the isthmus, has been available. The cost of each different project, and there have been sixteen different variants, has been estimated in detail, and a selection between them has thus been reached intelligently. The sum needed for the work of construction proper is, in round numbers, \$100,000,000. The element of time is more difficult to determine, but the volume remaining to be excavated at the Culebra being a little less than twelve million cubic meters (15,600,000 cubic yards), it is believed that ten years is a conservative esti-

NICARAGUAN DEMERITS. The Nicaragua Canal.-To the general relative merits of the two canals already considered may be added that the Panama merit of allowing the sills to be placed be- route lies in the interior of Colombia, while that by Nicaragua lies near the Costa Rican boundary, where hostilities are liable The volume of 1,000 cubic meters (35,300 at any time to cause difficulties, as they cubic feet) per second permitted to pass | already have done during the canal examination by the Walker commission last spring. Also that in respect to danger 1,200 cubic meters (42,360 cubic feet) allowed from possible earthquakes, which might easily cause trouble at the great locks, Panama is by far the more safe, because no active volcano is found within a distance of at least 200 miles from it, while three lie in the close vicinity of the route of the Nicat the sources of Rio Gigante, discharging aragua canal, and one within only forty miles of its western locks. Last April an earthquake destroyed substantial masonry buildings at Leon, only 100 miles distant

from these lock sites. But while it is thus easy to compare the two canals in their general features, and to see that the route by Panama is much superior to that by Nicaragua, when details are considered, we are confronted by the fact that really no definite project can be claimed for the latter. The company's project, as revised by the government commission, of which General Ludlow was president, is shown on the accompanying drawing, which may be compared with that given to illustrate the Panama project, but it should be noted that the latter has double the horizontal scale, thus failing to impress the eye by 50 per cent., with its relative merit in respect to length. The data upon which this project was based were so unsatisfactory to the Ludlow commission meters (213 feet), the crest being sixty-nine that they reported: "For obtaining the and Territory. The lime kilns and stone project, eighteen months' time, covering two dry seasons, and an expenditure of \$350,000, will be required." A new commission has been appointed, and new surveys inaugurated, and it appears from the views of the individual members, as given before the select committee of the Senate in June. 1898, that the changes undergoing study are radical in their nature, and that, although some at least of the engineering difficulties which impressed the former government commission are recognized as grave, no means of avoiding them have yet been discovered. Under these conditions it is anparent that confidence cannot be accorded to such a project, and that really there is only one canal, that of Panama, whose construction could be judiciously undertaken at the present time. It is to be hoped before the government embarks on so important a work that the relative merits of the two routes will be examined and judged by a commission of expert engineers, for it is certain that only one canal is now needed, and that that one should be the best possible.

In Benjamin's Own Town.

Philadelphia Record. A teacher of singing in one of the public schools attempted the other day to illustrate to her pupils just what was meant by time in asking if any of her pupils had ever was a dead silence. "Do you know what the pendulum of a clock is?" asked the teacher. Again there was a dead silence. "Has any member of the class ever seen a endulum?" was the next query. No member of the class ever had, so far as outward signs would indicate. The final question was: "Has any one ever heard of a pendu-The same period of silence ensued until a boy at the foot of the class began waving his hand frantically in the air "Well, James, have you ever heard of a pendulum?" asked the teacher. "Yes'm: Pendulum Franklin!" was the astonishing

The Peasant Girl. Beyond the sea he goes, beyond the sea Does he look back to Arcady and me? And yet, how could it be? How should he mate with such a maid as I? Ah, let him go-goodby!

Beyond my sight he goes, beyond my sight. Does he look back and say, "My sweet, good ald he know the pain I could not tell?

Beyond my prayer he goes, beyond my prayer. Does he look back from out the great world there? And yet, how could I dare? How should he know if love be wrong or right? Ah, let him go-good night!

UTICA, ON THE OHIO RIVER, HAS AN INTERESTING HISTORY.

Known as the "Lime Center" of the United States-Indians Terrifled

Correspondence of the l'dianapolis Journal. CHARLESTOWN, Ind., Nov. 20 .- Six miles southeast of the place the old county-seat of Clark county, and eight miles above Jeffersonville, on the Ohio river, is fied to stay on this side of the river. Them situated the quaint ad town of Utica, the big hills and dark ravines are only fit lime center of the United States. The only settlers who came from the beautiful Mohawk valley, in western New York, from and turning on his heel he walked briskly the vicinity of Utica, may possibly have away-to his old Kentucky cabin. flatboated down the had in mind as the? Ohio from Pittsburg the lines of the poet:

No pent-up Utica confines our powers, That is, they may have sung the above lines if not too busy flodging Indian arrows and bullets as they baddled downward toward the Falls of the Ohio.

From old-time records written by Samuel Morrison, who died at Indianapolis some twenty-five years ago, I am enabled to detail some interesting historical facts connected with early pioneer life in Clark county, Indiana, especially the vicinity of Utica. These old-time records are now in possession of Colf James M. Van Hook, of Charlestown, whi has given much attention to securing from the misty past many authentic stores of ploneer life, and is, indeed, Clark coulty's antiquarian.

There were origically two settlements made, one between the cliffs and the Ohio river, by James Noble Wood, in 1795, and another in the sare year on the north bank of the Ohio, apposite the mouth of Harrod's creek, Kentucky. At this period the present site of latica was a dense canebrake, which extended from the Ohio river back northwardly everal miles to Silver

The town of Utick was laid out in 1816 by Judge James Noble Wood, Judge John Miller and Dr. Samuel Bleight, of Philadelphia. Dr. Bleigh contracted with James Ferguson to build one hundred cabins of round logs, with wapboard roofs, at \$25 each. Samuel Morraon, from whose papers this sketch is comfiled, arrived at Utica in September, 1817, finding all these cabins completed and some of them occupied. Mr. Morrison was Utices first school teacher, and remained in the little town about seven much of its pioneer history.

In 1819 four additional families arrived at Utica from Philadelshia. Among them was Evan Thomas, a sone mason, who built the first three store houses in the town. What Utica stone has since produced in the way of lime and cereent has been enormous. "U. T. K." lime is known in every State river just above Natchez, which is known necessary data for the formation of a final quarries are not reached by any line of railroad, but all shipments are made by steamboat and the regulation lime boat. Utica lime is often aughingly alluded to as the "poor man's a paint." The colored brother who manifulates the whitewash brush is frequently called "the exterior decorator" when feeces and outbuildings in spring take on a foat of dazzling whiteness, the result of his skill. THE LAST MAMMOTH.

Samuel Morrison's records tell the following story, which the author had from the lips of old father John McClintock, in the early days of Utica

other men were brigging two large pirogues

McClintock and eight

In 1783 John

loaded with flour, pacon and whisky, the "staffs of life" in that day, from old Fort Redstone, to the fourth of Fourteen-mile creek, fourteen mil's above the Falls of the Ohio. When they were about half a mile above the mouth of the creek some animal of enormous size Intered the river from the Kentucky shore. It threw the water so high that they could not see its shape or size, and it stirred up the mud from the very bottom of the river, making the stream so rough tey had to land to keep from sinking. The animal went out into the mouth of Fourseen-mile creek, but just at that time the boatmen imagined they heard the yells of Indians, so they pushed out into the river for safety. Several of the men wanted to return and see the animal's tracks, but were refused permission by Commander McClintock. It was generally believed in the Utica settlement and is to this day that Captain McClintock and his men had w tnessed the departure of

the last mammoth John Lentz was the second merchant in Utica, and built the first steam grist mill. Samuel McClintock kept the first and only tavern in the town Judge Wood operated ferry opposite the Flouth of Harrod's creek. Thomas Worrall, who lived on the Kentucky shore, just selow the mouth of Harrod's creek, also overated a ferry from that side of the river.

Battle creek, a shift stream which rushes into the Ohio at the foot of Twelve-mile island, was famed from the earliest days for its many sanginary conflicts between the red man and nis pale-faced brother. It was a great cressing of emigrants from Kentucky to Indiana. Indiana lands were selling for \$1.25 per acre, and many Kentuckians tock advantage of the low prices and found homes on Hoosier soil.

TOWN Indianians imagined they had settled on a soil not adapted to wheat growing bence soil not adapted to wheat growing, hence sold their holdings at a sacrifice in order to locate in the highlands, or knob country, which was a mistake. But they did discover that the highlands were admirably adapted to fruit culture, being above the line of late spring frosts, which nearly every time caught the fruit buds in the river lowlands.

One day a tall, lank Kentuckian of the corn-cracker variety, came to Thomas Worrall's to make some inquiries and be 'set across the river." Day was just dawning, and the Kentuckian stood on the river shore for some time gazing with am zement on the frowning cliffs and precipitous bluffs about Utica. Finally, turning to Worrall, the Kentuckian said: I won't go over thar. I've looked over the d-d country at this distance, and I'm satisplaces for thieves. Indians and wild varmints, and I won't risk my life among 'em,"

A STRANGE SCALPING STORY. From the valuable manuscript in possession of Colone! Van Hook is condensed the following remarkable story connected with the early history of Clarksville, now known as Ohio Falls: In the spring of 1790 a family of the name

of Smith emigrated from Pennsylvania and settled at Clarksville, with some half dozen other families, and a company of troops under the command of Capt. Robert George. They at once erected a stockade, keeping the families closely confined therein, as prowling bands of Indians were very numerous. The water used in the stockade was brought from a spring nearly a quarter of a mile distant. The oldest daughter of Mrs. Nancy Smith, about twelve years of age, was sent one day to the spring for water. Just as she had filled her bucket she was fired upon by seven Indians who lay in ambush. The girl fell, and the savages ran to her and removed her scalp, but did not sink the tomahawk into her brain. as was their usual custom. The men in the stockade, hearing the firing, hurried to the spring, where they found the girl weltering in her blood, and, as they thought, dead. Closer investigation revealed the astonishing fact that she was still alive, She was able to describe the savages and how they looked. Seven balls had passed through her body, but none had touched a vital spot.

Careful nursing enabled the girl to recover from her terrible injuries, though it was recorded as a miracle, and in a few months she was able to walk about the stockade again. And now comes the strange part of the story. The badly wounded scalp healed over, but instead of hair of the years, picking up and stringing together natural color the growth was of a snowy whiteness and as coarse as the hair of a

> Miss Smith, at sixteen years of age, was united in marriage to a Mr. Fairchild, and herself and husband at an early day removed to Mississippi Territory and purchased the large island in the Mississippi to this day as Fairchild's island. Here they lived, prospered and reared a large

> Mrs. Fairchild visited Utica for the last time in 1823, where her aged mother and her only sister, Mrs. James Noble Wood, then resided. She was then a hale and hearty matron, and conversed freely and intelligently of the early days of Clark's grant, of General George Rogers Clark, and his brother, General William Clark, who surveyed the grant and afterwards went on an exploring expedition to the mouth of the Columbia river in company with Merriwether Lewis, the travels of these pathfinders revealing the greatness and possibilities of the Louisiana Purchase, whose glories we are to celebrate next year by the great exposition and world's fair at St

Mrs. Fairchild, while on this last visit to Utica, exhibited her scalped head to several of her intimate friends, and though thirty-three years had passed since that fearful experience at Clarksville, the scalped spot and its curious growth of white, coarse hair was still as much in evidence as at the time which witnessed WILL DIETZ. its appearance.

Snake Attacks Auto Party.

New York Herald. Mr. and Mrs. James Davidson and Mr. and Mrs. George W. Monson, of New York, who have been at their summer homes in Denville, N. J., on a hunting trip, had a battle with snakes yesterday morning at Min Hill while touring through German Valley and Newfoundland in an automo-

The reptiles, two copperheads, were coiled up in the middle of the road ready to spring. The big automobile was moving rapidly, and its wheel struck one of the snakes, killing it instantly. Snake No. vanished. The occupants of the vehicle could not tell where the thing had gone, so sudden had been its disappearance. When the party reached Denville Junction a railroad gateman called to them that snake was on the rear wheel and had a ferry above Ution, and Judge Miller the curled itself around the spokes. The machine was stopped and the snake stuck its head up in front of Mr. and Mrs. Monson,

who were in the front seat. Mrs. Monson screamed and jumped out of the automobile into a brook, sinking in mud and water over the shoe tops. She then ran over to the crossing gate shanty and grabbed a broom from Harry Riker. the gateman. When Mrs. Monson was about to strike the reptile it suddenly opened its mouth and made a dash at her. It chased her into the shanty, when she got the door partly closed on its head. The men of the party killed the snake with their guns and threw it into the brook. The snake was about three feet long. Riker, the gateman, received \$15 for discovering the snake, which might have dor serious harm if it had not been detected i